

# ATM passive optical network dual system and method, optical path terminal and network unit

**Patent number:** CN1338832  
**Publication date:** 2002-03-06  
**Inventor:** KOSHI NAKAISHI (JP)  
**Applicant:** NIPPON ELECTRIC CO (JP)  
**Classification:**  
- international: H04Q11/00; H04Q11/04; H04L12/56; H04Q11/00;  
H04Q11/04; H04L12/56; (IPC1-7): H04B10/12;  
H04L12/28  
- european: H04Q11/00P4; H04Q11/04S2  
**Application number:** CN20010124059 20010810  
**Priority number(s):** JP20000243029 20000810

## Also published as:

EP1179965 (A2)  
US2002021472 (A1)  
JP2002057679 (A)  
EP1179965 (A3)


Report a data error here

Abstract not available for CN1338832

Abstract of corresponding document: **EP1179965**

An ATM dual system wherein the intervals between couplers and ONUs are dualized comprises a dualized line termination device loading a PLOAM cell transmitter/receiver within an OLT, the PLOAM cells being used for monitoring and being transmitted and received between the OLT and the ONU, and a PST message transmitter/receiver which loads and allocates switch controlling information to K1/K2 byte areas of the aforementioned PLOAM cells, and a VP/VC switch which switches each of the relevant VP or VC on the basis of the aforementioned K1/K2 byte information.

FIG. 7



Data supplied from the esp@cenet database - Worldwide

BEST AVAILABLE COPY